

FO connectors - VS-V1-C-LC-MNNA-PG9-A1-G - 1419190

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



LC fiber optic connector, IP67, with bayonet locking, metal housing, duplex, with adhesive connection technology, for multi-mode fiber, for cable diameter of 5.0 mm ... 10 mm

Product Features



EtherNet/IP

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	140.0 GRM
Custom tariff number	85366990
Country of origin	Germany

Technical data

Mechanical characteristics

Number of positions	2
Number of slots	1
Locking type	Bayonet locking
Fiber type	Multi-mode 50/125 µm fiberglass
Insertion/withdrawal cycles	500
Connection method	LC
Max. cable diameter	5 mm ... 10 mm
Color	silver

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Degree of protection	IP67

Material data

Housing material	Zinc die-cast
------------------	---------------

FO connectors - VS-V1-C-LC-MNNA-PG9-A1-G - 1419190

Technical data

Material data

Material	Metal
----------	-------

Electrical characteristics

Number of positions	2
---------------------	---

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260709
eCl@ss 7.0	27440305
eCl@ss 8.0	19170122

ETIM

ETIM 2.0	EC001122
ETIM 3.0	EC001122
ETIM 4.0	EC001122
ETIM 5.0	EC001122

UNSPSC

UNSPSC 6.01	30211832
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	39121429

Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

FO connectors - VS-V1-C-LC-MNNA-PG9-A1-G - 1419190

Approvals

Approvals submitted

Approval details

EAC

EAC

Drawings

Dimensional drawing

