

Electronic housing - ME 67,5 UT/FE BU - 2278597

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Component housing, Lower part, Color: blue, Width: 67.5 mm, Constructional height: 114.5 mm

Product Features

- Tool-free mounting
- 2 optional serial contacts (daisy chain)
- Low design width with a high number of positions
- Gold contacts for data transmission and power supply (125 V, 8 A)
- Large assembly area
- Can be snapped onto standard NS 35/7,5 and NS 35/15 DIN rails
- Recessed labeling areas
- Supply via standard MINI COMBICON plug
- Same PCB geometry for all design widths
- Inflammability class V0 according to UL 94
- Fast mounting on DIN rails according to EN 60715
- Material and part identification embossed on the housing (recyclability)
- Cost savings thanks to easy device production
- Functional earth ground contact (EMC) integrated in the housing base
- Electronic components can be partially removed
- Optional BUS connection integrated in the housing, for either parallel or serial contacting
- Metal foot catch

Key commercial data

Packing unit	1 1
Minimum order quantity	250 1
Weight per Piece (excluding packing)	80.98 GRM
Custom tariff number	85472000
Country of origin	Germany

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702

Electronic housing - ME 67,5 UT/FE BU - 2278597

Classifications

eCl@ss

eCl@ss 8.0	27182702
------------	----------

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized 
