


Programming Specification

OPERATING PARAMETERS

Input Clock (MHz)	CLoad	FSEL	CLK0			CLK1			Operating Voltage (V)
			Frequency (MHz)	Accuracy (ppm)	Output Drive Strength (mA)	Frequency (MHz)	Accuracy (ppm)	Output Drive Strength (mA)	
24	18 pF	1 (Default)	24	0	Std, (10mA)	24.576	0	Std, (10mA)	2.5 & 3.3
		0	24		Std, (10mA)	22.5792		-11.19	

PIN DESCRIPTION

Name	Pin #	Type	Description	Package Pin Configuration
XIN	1	I	Crystal Input	
GND	2	P	GND Connection	
CLK0	3	O	Programmable Clock Output	
CLK1	4	O	Programmable Clock Output	
VDD	5	P	VDD Connection	
NC	6	-	NC Connection	
FSEL	7	I	Frequency Select Input	
XOUT	8	O	Crystal Output	

Note: please refer to Micrel's PL611-01 datasheet for detailed electrical specifications.

ORDERING /SHIPPING INFORMATION

Package Option	Temp. Range	Shipping Method
MSOP-8L	Commercial	Sample Box

Part/Order Number	Verification Code	Marking
PL611-01-N12MC	FSel0=28-13-8F-19-12-00-01-AE-21, FSel1=25-19-80-19-12-00-01-AE-23	

For Package/Marking specifications please see [Packaging Spec.](#)

Note: LLL / LLLLL designate Production Lot.

Micrel Inc, reserves the right to make changes in its products or specifications, or both at any time without notice. The information furnished by Micrel is believed to be accurate and reliable. However, Micrel makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon this product.

LIFE SUPPORT POLICY: Micrel's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of Micrel Inc.