



#### General ordering data

Order No.	8237720000
Part designation	WOS2 24VUC 4C
Version	WAVE-Series, Optos, 12 V DC ... 24 V DC ... 28 V DC, 0.5 A per channel, Screw connection
EAN	4032248017744
Qty.	1 pc(s).

#### Dimensions

Clamping range, nom.	1.5 mm <sup>2</sup>
Clamping range, min.	0.5 mm <sup>2</sup>
Clamping range, max.	2.5 mm <sup>2</sup>

#### temperature

Ambient temperature (operational)	-25 °C...+50 °C
Storage temperature	-40 °C...+85 °C

#### Approvals

Approvals institutes	CSA; CURUS; GOSTME25; CE
----------------------	--------------------------

#### Control side

Power rating	0.4 VA / 0.3 W
Rated auxiliary voltage	No
Rated control voltage	18 V UC...30 V UC

#### General data

Standards	EN 50178
Humidity	40°C / 93% rel. humidity, no condensation
Conductor connection system	Screw connection
DIN Rail compatibility	TS 35

#### Insulation coordination (EN 50 178)

Clearance and creepage distances for control/load side	≥ 3 mm
Overvoltage category	III

#### Insulation coordination (EN 50 178)

Pollution severity	2
Rated impulse withstand voltage	6 kV
Rated voltage	150 V

#### Load side

Protective circuit	Varistor, reverse polarity protection
Rated auxiliary voltage	No
Rated switching current	0.5 A per channel
Rated switching voltage	12 V DC ... 24 V DC ... 28 V DC
Short-circuit-proof	Yes
Status indicator load side	LED green in output
Switch-off delay	< 50 ms
Switch-on delay	< 20 ms

#### Classifications

ETIM20	EC001504
ETIM30	EC001504
eClass 4.1	27-27-09-00
eClass 5.0	27-27-09-90
eClass 5.1	27-27-09-90
eClass 6.0	27-27-09-90

#### Similar products

Order No.	Part designation	Version
-----------	------------------	---------