


SECTION A-A



SECTION B-B

PART NO.	a	b	Rc	d	e	Rf	WIRE RANGE (mmSQ)	Q'TY/REEL	FINISH	REMARK (OPTION)
35427-9700									UNPLATED	---
-9702	S	2.8	2.8	0.9	3.8	3.8	0.3 ± 0.5	5000	PLATED	---
-9710									UNPLATED	MARK "H"
35427-9800									UNPLATED	---
-9802	M	3.0	3.5	1.2	5.0	5.0	0.85 ± 1.25	5000	PLATED	---
-9810									UNPLATED	MARK "H"
35427-9900									UNPLATED	---
-9902	L	5.2	4.6	2.0	6.3	6.3	2.0 ± 3.0	4000	PLATED	---
-9910									UNPLATED	MARK "H"

NOTES

1. MATERIAL : BRASS (C2600), THICK = 0.35mm

2. TENSION (35427-970*,980*,990*)

- INSERTION FORCE(INITIAL) : 1.0 ± 1.5 Kgf

- WITHDRAWAL FORCE(6 TIMES) : 0.6Kgf MIN.

△ TENSION (35427-971*,981*,991*) "H" MARK

- INSERTION FORCE(INITIAL) : 1.5 ± 2.0 Kgf

- WITHDRAWAL FORCE(6 TIMES) : 0.8Kgf MIN.

ADDED TENSION & MARK EC NO. KOR2000-0068 DRWN: B.C.YOON 00/10/25 CHK: B.K.CHOI 00/10/25 APPR: C.W.LEE 00/10/25	QUALITY SYMBOLS MAJOR ▽ = 0 CRITICAL ▽ = 0	GENERAL TOLERANCES: (UNLESS SPECIFIED)		SCALE 5:1	DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	DIMENSIONS: <input type="checkbox"/> mm <input type="checkbox"/> INCH <input checked="" type="checkbox"/> mm ONLY	SHT REV REVISE ON CAD ONLY
		4 PLACES ±0.	mm	INCH	DRAWN BY & DATE J.K.OH 96/10/11		
		3 PLACES ±0.			CHECKED BY & DATE B.KCHOI 96/10/11		
		2 PLACES ±0.			APPROVED BY & DATE C.W.LEE 96/10/11		
1 PLACE ±0.3			CAD FILENAME sd35427.dgn	MATERIAL NO. 35427-9***	DRAWING NO. SD-35427-002	SHEET NO. 1 OF 1	
REV		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.			SIZE B