

Specification Sheet

Part Number: 594-03000



Laser Tag Label, 3.5" x .50", For Fiber Distribution Chassis, PET, White, 1000/pkg

Article Number	594-03000
Type	FDCLASER
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">•White polyester has a smooth surface, allowing for the highest resolution and print contrast.•The acrylic-based adhesive bonds to a wide variety of substrates and resists abrasion.•LaserTags are sheet fed for easy loading and fast printing.
Quantity Per	pack

Product Description

HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 788 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, general purpose marking.

Short Description	Laser Tag Label, 3.5" x .50", For Fiber Distribution Chassis, PET, White, 1000/pkg
Global Part Name	FDCLASER-788-WH
Width W (Imperial)	3.5
Width W (Metric)	88.9
Thickness T (Metric)	64.0
Height H (Imperial)	0.5
Height H (Metric)	12.7
Width of Liner (Metric)	279.4
Width of Liner (imperial)	11.0
Material	Type 788, Polyester (PET)
Material Shortcut	788
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +199°F (-40°C to +93°C)

Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919905060
Labels per Column	2
Labels per Row	20
Weight (Metric)	0.521
Weight (Imperial)	1.14