

## Housing - HC-HV 6-TMQ-65/M1PG21S - 1773747


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Hood, with double locking latch, height 65 mm, with screw connection, 1x Pg21, lateral cable entry

The illustration shows a sleeve housing in the versions for double locking latch and single locking latch and with double locking latch, with straight cable exit

### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 115685
Weight per Piece (excluding packing)	390.21 GRM
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### Dimensions

Height	65 mm
Width	43 mm
Length	94 mm
Wrench size, union nut	28 mm
External cable diameter	10 mm ... 19 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

Note	For contact inserts HV-HV6
Type	HV6

# Housing - HC-HV 6-TMQ-65/M1PG21S - 1773747

## Technical data

### General

Housing type	Sleeve housing
Locking type	With double locking latch
No. of cable outlets	1
Cable exit	Lateral
Screw connection	with
Type of the screw connection	1x Pg21
Housing material	Aluminum die-cast
Housing surface material	Powder-coated, gray
Cable gland material	Nickel-plated brass
Cable seal material	NBR
Material lock	High-grade steel
Material grip body interlock	PA-GF

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440202

### ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

## Housing - HC-HV 6-TMQ-65/M1PG21S - 1773747

### Approvals

Approvals

---

Approvals

GOST

---

Ex Approvals

---

Approvals submitted

---

### Approval details

