



Cat. 6A RJ45 Plug  
(Strain Relief, Plastic,  
or Metallized Plastic  
with M28 Threads)

Cat. 6A RJ45 Plug (Standard)

**Notes:**

1. Electrical:
  - Meets EIA/TIA-568-B.2-10 Cat.6A Channel Specification
  - Connector Operating Temperature: -40~C to +85~C
2. Materials and Finish:
  - Coupling Ring: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
  - Plug Housing: Polyester (Black) or Metallized ABS (Nickel Plated); UL94 V-0
  - Interfacial Seal: Silicon, Color: White
  - Cable Gland: PA (Black) or Brass, Nickel Plated
  - Cable Gland Seal: NBR, Color: Black
  - Cable Gland Insert (Metal Version): Nylon, Color: White
  - Cat.6A RJ45 Plug Metal Shell: Copper Alloy, Nickel Plated
  - Cat.6A RJ45 Plug Plastic Housing: Clear Polycarbonate UL94 V-2
  - Cat.6A RJ45 Plug Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
  - Cable: Cat.6A SSTP, 4 Pairs, AWG26, Stranded, Jacket Color: Black
  - RJ45 Modular Boot: PVC, Color: Black
3. RoHS compliant

Directive 2002/95/EC RoHS Compliant

Cable Length <b>L</b>	Plastic Version	Metallized Plastic Version
2 m	17-150664	17-150694
4 m	17-150674	17-150704
5 m	17-150684	17-150714

Note: Special cable length are available, please contact factory

THIS DRAWING MAY NOT BE COPIED, OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION <b>DO NOT ALTER CAD DRAWING BY HAND</b>	Customer:			Tolerance Unless otherwise specified 0 PLC ±0.50 1 PLC ±0.38 2 PLC ±0.25 3 PLC ±0.10 ANGLES ±3°		Scale:	Dim. in meter	
	Name	Title	Approval Date			Material: See Notes		
				2011	Date	Name	Cat.6A RJ45 Ethernet Patch Cords Strain Relief to Standard	
				Draw.	Sept. 22	Vincent Ke		
				Appd.	Sept. 22	J. Chaudry		
				Norm		Drawing No.: 17k1A277		
				D-old				
	a	original				Part No.: SEE PART NUMBER TABLE		
	Rev.	Changes	Date	Name			DIN A3	
							Sheet 1/1	