

## Specification Sheet

Part Number: T150L0X2



Heavy Duty Cable Tie, 32.3" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 25/pkg

Article Number	111-15405
Type	T150L
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>•Engineered and manufactured for maximum performance and quality.</li><li>•Made from 100% high-quality plastic to ensure efficient recycling.</li><li>•Inside serration for a strong hold onto bundles.</li><li>•Easy application either manually or with a tensioning tool.</li><li>•Bent tail allows for simpler insertion.</li></ul>
Quantity Per	bag
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description**

Heavy Duty Cable Tie, 32.3" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 25/pkg

**Global Part Name**

T150L-PA66-BK

**Minimum Tensile Strength (Imperial)**

175.0

**Minimum Tensile Strength (Metric)**

780.0

**Length L (Imperial)**

32.3

**Length L (Metric)**

820.0

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.35

**Width W (Metric)**

8.9

**Bundle Diameter Min (Imperial)**

0.32

**Bundle Diameter Min (Metric)**

8.0

**Bundle Diameter Max (Imperial)**

9.6

**Bundle Diameter Max (Metric)**

243.8

<b>Thickness T (Metric)</b>	1.9
-----------------------------	-----

<b>Material</b>	Polyamide 6.6 (PA66)
-----------------	----------------------

**Material Shortcut** PA66

<b>US MIL SPEC</b>	MIL 53421	<b>Flammability</b>
--------------------	-----------	---------------------

UL 94 V2

**Halogen free**

Yes

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Certification/Specification WEB**

UL | ANSI/UL 1565 UL | ANSI/UL 62275 UL | ANSI/UL 746B

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

<b>Package Quantity(Imperial)</b>	25
-----------------------------------	----

**Package Quantity (Metric)** 25

<b>Customs Number</b>	3926909987
-----------------------	------------

