DRAWING MADE IN THIRD ANGLE PROJECTION

PART NUMBER	REV	FIRST USED
565486-5	A	1-471273-2

AMP 1261 7/93

APPLICATOR PARTS LIST

TYPE: 30° ROTATED STRAIN RELIEF

NO.	DESCRIPTION	REQ.	PART NO.
1	△1 WIRE CRIMPER	–	–
2	△1 INS CRIMPER	1	386993-8
3	△1 ANVIL	1	1-694325-0
4	ANVIL, SPACER	1	453263-1
5	△1 FLOATING SHEAR	1	473243-2
6	△1 REAR SHEAR PLATE	–	–
7	SHEAR BLADE MT BLK	1	386442
8	△1 FRONT SHEAR PLATE	1	386414
9	REAR ANVIL SPACER PLATE	–	–
10	FRONT ANVIL SPACER PL		
11	TOOL SPACER	1	370691
12	CRIMP SPACER	–	–
13	FRONT STRIP GUIDE	1	386444-3
14	REAR STRIP GUIDE	1	1-465350-5
15	RAM	1	471167
16	TOOL HOLDER	1	461347-1
17	ADJ CRIMP MOUNT	–	–
18	ADJ BLOCK	–	–
19	APPLICATOR MOUNT ASSY.		
20	BASE PLATE	1	463110-1
21	BASE BLOCK	1	473227
22	STRIP GUIDE PLATE	1	453689-1
23	ANVIL HOLDER	–	–
24	AUX. ANVIL HOLDER	–	–
25	STRIPPER	1	694924-1
26	STRIPPER MOUNT	–	–
27	RETAINER PLATE		
28	STRIPPER MOUNT BRACKET		
29	STRIPPER BUSHING	–	–
30	STOCK DRAG	1	387650-4
31	STOCK DRAG NUT	1	21018-5
32	STOCK DRAG STUD	1	800849
33	STOCK DRAG SPRING	1	370572
34	STOCK DRAG ADJ. SCREW	1	2-21006-9
35	FEED FINGER HOLDER	1	386942
36	FEED FINGER	1	473739-1
37	FEED FINGER TIP	1	387251
38	FEED FINGER GUIDE	1	693680-2
39	BASE CASTING	1	565147-2
40	GUARD	1	461343-4
41	–	–	–

NO.	DESCRIPTION	REQ.	PART NO.
42	SHEAR DEPRESSOR	1	810955-5
43	△1 SPRING, SHEAR	1	386455
44	SPRING SEAT	1	386443
45	SHEAR BEARING PLATE, FRT	1	386409-1
46	REAR OILITE BEARING PLT	1	386408
47	LEFT OILITE BEARING PLT	1	386406
48	RIGHT OILITE BEARING PLT	1	386407
49			
50			
51	STRIP HOLD	1	692871-1
52			
53			
54			
55	PLATE, IDENTIFICATION	1	464249-1
56			
57			
58			
59			
60			
61	MOUNT, REEL BRK, 30°	1	453602-1
62			
63	SPACER, AIR FEED	1	460590-1
64	1" AIR FEED ASSY	1	690021-1
65	TENSION ADJ PLATE	1	374999
	MISCELLANEOUS		
66	LUBRICATOR ASSY	1	465184-2
67	–	–	–
68			
69	–	–	–
70	–	–	–
71			
72			

FOR HARDWARE SEE 687514-6.

CRIMPING DATA				TERMINALS
TO APPLY TERMINAL				J-HOOK
				61828
WIRE SIZE	CRIMP HEIGHT			62264
.090 X .140	.125 △2			62362
CRIMP	SIZE	TYPE	FEED	
INS.	.220	0	.660 OR .908	WING
WIRE	–	–		61831
SLEEVED	OVER FLAT ANVIL			
INSULATION RANGE	WIRE RANGE			
.120-.180	–			
EXPLODED VIEW A-6009-3				RING
REMARKS:				61520
TOP TOOL MOUNTING SEQUENCE				62245
ITEM 42, 11 & 2				
△2 WIRE SIZE				
.140				HOOK
				61522
.090				

△1 RECOMMENDED SPARE PARTS.

P	F	LTR	REVISION RECORD	APP	DATE
		A1	0150-6796-96	CE	4-96

565486-5

DIMENSIONS IN INCHES.
DO NOT SCALE PRINT.
TOLERANCES UNLESS OTHERWISE SPECIFIED:
2 PLC DEC ±-
3 PLC DEC ±-
4 PLC DEC ±-
ANGLES ± -
SURF TEXTURE: √
REMOVE BURRS, BREAK SHARP EDGES R.015 MAX

MATL – –	HT TR – –	FIN – –
DR 4-17-96 D.SALTZER	APP 4-19-96 T.ELBIN	AMP Incorporated Harrisburg, PA 17105-3608
CHK 4-19-96 C.ERISMAN	REL 5/14/96 B. MORGAN	
NAME SIDE FEED STD APPLICATOR		MACHINE REF STD-APPL
SCALE 1:1	B DWG NO 565486-5	SHEET 1 OF 1 REV A1

LOC A
DIST 4

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN AMP PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM AMP INCORPORATED, HARRISBURG, PA.