


Fuse terminals

SAKS 3 SAKS 3/35



Dimensions/approvals	
Width/length/height (mm)	with TS 32 13/54/61
Width/length/height (mm)	with TS 35 x 7.5 13/54/55
Insulation stripping length/clamping screw/screwdriver blade	12 mm/M 4/5.5 x 1

Rated data/feed through-terminal base	
Rated voltage/current/cross-section	500 V/10 A/10 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Further technical data	
Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4

Clampable conductor	
Solid H07V-U	mm ² 0.5...16
Stranded H07V-R	mm ² 1.5...10
Flexible H07V-K	mm ² 0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...10
Plug gauge according to 60 947-7-1	Size B 6
Continuous current rating of cross-connection 2...5-pole	A (QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A (QL 6...10) 36

Rated data according to UL/CSA	
Voltage/current/conductor size	UL 300 V/10 A/22...10 AWG
Voltage/current/conductor size	CSA 600 V/10 A/22...10 AWG

Ordering data	
Version	Qty. Qty.
KrG	0248920000 ³⁾ 20 0667520000 ³⁾ 20
KrG	0297520000 ⁴⁾ 20 0328920000 ⁴⁾ 20

End plate/partition (thickness mm)	
PA	Type Cat. No. Qty. AP (2.5) 0191320000
HP	for TW (2.0) 0607000000



Fuse inserts	
1 1/4" x 1/4"	Nominal current (A): 0.5 fast
	1.0 fast
	2.0 fast
	3.0 fast
	5.0 fast
	7.0 fast
	10.0 fast

G fuse inserts 5 x 30 mm (500 V~/0.032...6.3 A).
Available from Wickmann-Werke GmbH,
Annstr. 113, 58453 Witten, Germany, Phone ++492302/6620

D fuse inserts	
	Rated voltage 400 V
	E 14/2 0137400000 10
	E 14/4 0137500000 10
	E 14/6 0328300000 10
	E 14/10 0328400000 10
	E 14/16 0328500000 10

Screw cap (spare)	
red	SK (5 x 30) 0282000000 20
black	SK (1/4"x1 1/4") 0428900000 20

Marking tags	
	DEK Standard DEK 5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"
*only for TS 32

SAKS 4 SAKS 4/35



Width/length/height (mm)	24/75/73
Width/length/height (mm)	24/75/66
Insulation stripping length/clamping screw/screwdriver blade	14 mm/M 4/5.5 x 1

Rated voltage/current/cross-section	400 V**/16 A/10 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4

Clampable conductor	
Solid H07V-U	mm ² 0.5...16
Stranded H07V-R	mm ² 1.5...10
Flexible H07V-K	mm ² 0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...10
Plug gauge according to 60 947-7-1	Size B 6
Continuous current rating of cross-connection 2...5-pole	A (QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A (QL 6...10) 36

Rated data according to UL/CSA	
Voltage/current/conductor size	600 V/30 A/22...8 AWG

Ordering data	
Version	Qty. Qty.
KrG	0321320000 20 0501820000 20
KrG	0297520000 ⁴⁾ 20 0328920000 ⁴⁾ 20

End plate/partition (thickness mm)	
Neozed D 01	Type Cat. No. Qty. TW HP (2.0) 0607000000 * 20

QL 2	0328000000 20
QL 3	0328100000 20
QL 4	0328200000 20
QL 10	0339000000 20

SS M 4	0136400000 100
BS M 4x9	0103300000 100

Fuse insert	
Amp. Colour Cat. No. Qty.	
P 14/2 prk	0138000000 50
P 14/4 brown	0138100000 50
P 14/6 green	0328600000 50
P 14/10 red	0328700000 50

Rated voltage 400 V	
E 18/20	0361300000 10
E 18/25	0361400000 10
E 18/35	0361500000 10
E 18/50	0361600000 10
E 18/63	0361700000 10

SK	0339410000 20
----	----------------------

DEK 5	see "Accessories"
-------	-------------------

SAKS 5 SAKS 5/35



Width/length/height (mm)	28/80/80.5
Width/length/height (mm)	28/80/66
Insulation stripping length/clamping screw/screwdriver blade	13 mm/M 4/5.5 x 1

Rated voltage/current/cross-section	400 V/63 A***/16 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4

Clampable conductor	
Solid H07V-U	mm ² 1.5...16
Stranded H07V-R	mm ² 1.5...16
Flexible H07V-K	mm ² 1.5...16
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 1.5...16
Plug gauge according to 60 947-7-1	Size B 7
Continuous current rating of cross-connection 2...5-pole	A (QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A (QL 6...10) 36

Rated data according to UL/CSA	
Voltage/current/conductor size	600 V/63 A/14...6 AWG

Ordering data	
Version	Qty. Qty.
KrG	0359420000 20 0502120000 20
KrG	0297520000 ⁴⁾ 20 0328920000 ⁴⁾ 20

End plate/partition (thickness mm)	
Neozed D 02	Type Cat. No. Qty. TW HP (2.0) 0607000000 * 20

QL 2	0207800000 20
QL 3	0207900000 20
QL 4	0208000000 20
QL 10	0338900000 20

SS M 4	0136400000 100
BS M 4x9	0103300000 100

Fuse insert	
Amp. Colour Cat. No. Qty.	
P 18/20 Blue	0361800000 50
P 18/25 yellow	0361900000 50
P 18/35 black	0362000000 50
P 18/50 white	0362100000 50

Rated voltage 400 V	
E 18/20	0361300000 10
E 18/25	0361400000 10
E 18/35	0361500000 10
E 18/50	0361600000 10
E 18/63	0361700000 10

SK	0359310000 20
----	----------------------

DEK 5	see "Accessories"
-------	-------------------

SAKS 2 SAKS 2/35



Width/length/height (mm)	28/80/81.5
Width/length/height (mm)	28/80/75
Insulation stripping length/clamping screw/screwdriver blade	12 mm/M 4/5.5 x 1

Rated voltage/current/cross-section	500 V/10 (25) A***/10 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4

Clampable conductor	
Solid H07V-U	mm ² 0.5...16
Stranded H07V-R	mm ² 0.5...10
Flexible H07V-K	mm ² 0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...10
Plug gauge according to 60 947-7-1	Size B 6
Continuous current rating of cross-connection 2...5-pole	A (QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A (QL 6...10) 36

Rated data according to UL/CSA	
Voltage/current/conductor size	600 V/25 A/22...8 AWG

Ordering data	
Version	Qty. Qty.
KrG	0206820000 20 1368720000 20
KrG	0297520000 ⁴⁾ 20 0328920000 ⁴⁾ 20

End plate/partition (thickness mm)	
Diazed E 16	Type Cat. No. Qty. TW HP (2.0) 0607000000 * 20

QL 2	0207800000 20
QL 3	0207900000 20
QL 4	0208000000 20
QL 10	0338900000 20

SS M 4	0136400000 100
BS M 4x9	0103300000 100

Fuse insert	
Amp. Colour Cat. No. Qty.	
P 16/10 red	0208900000 100
P 16/16 grey	0209000000 100
P 16/20 Blue	0209100000 100

Rated voltage 500 V	
E 10 A	0208500000 25
E 16 A	0208600000 25
E 20 A	0208700000 25
E 25 A	0208800000 25

SK	0284110000 20
----	----------------------

DEK 5	see "Accessories"
-------	-------------------

** Also for 440 V- with neozed marina fuse
*** Current for overload up to 10 A, for short circuit up to 25 A

3) For fuse inserts 1 1/4" x 1/4" DEF 63
4) For fuse inserts 5 x 30