



1) Markierung erster Kontakt, Ader 1 des Flachkabels
 1) Contact no.1, 1st wire of flat cable
 1) Contact no.1, repère 1 du câble

| | | | | | | | | | | |
|----------------|--------------------------------------|---|----------------------------------|---|--------------------------------|------------------|-----------------------------------|---|--|----------------------|
| A | 09 18 526 5813 58U | 0,76 μm Au | Bulk packaging MOQ = 1500 pcs | All Dimensions in mm Original Size DIN A 4 | Techn. Character. | | | Nicht tolerierte Maßel Free size tolerances | | |
| | 09 18 526 6813 58U | 2 | | | | | | | SEK 18 Female connector 26 poles with central polarisation without cable stop with strain relief | |
| | 09 18 526 7813 58U | 3 | | | | | | | | |
| | 09 18 526 5813 | 0,76 μm Au | N.A. | | | | | | | |
| | 09 18 526 6813 | 2 | N.A. | | | | | | | |
| 09 18 526 7813 | 3 | N.A. | | | | | | | | |
| | Bestell-Nr. Part-No. Reference | Anforderungsstufe performance level Niveau de qualite | Index Designation | 36265 26570 Mod. | 30-SEP-11 01-FEB-00 Dat. | BH JB Name | HARTING EURL F-95972 Paris | | TB 0918526X813 Sub. | Blatt/ page 1 / 1 |