



WIRING TABLE

	C1		C2		C1		C2
	1	————	1		10	————	10
	19	————	19		28	————	28
	2	————	2		11	————	11
	20	————	20		29	————	29
	3	————	3		12	————	12
	21	————	21		30	————	30
	4	————	4		13	————	13
	22	————	22		31	————	31
	5	————	5		14	————	14
	23	————	23		32	————	32
	6	————	6		15	————	15
	24	————	24		33	————	33
	7	————	7		16	————	16
	25	————	25		34	————	34
	8	————	8		17	————	17
	26	————	26		35	————	35
	9	————	9		18	————	18
	27	————	27		36	————	36
					shell	Cable Braid	shell

NOTES /

- 1.) MECHANICAL REQUIREMENTS
- OPERATING TEMPERATURE = -35° TO +80°C
- 2.) WHITE LABEL INFORMATION:

DATE CODE & LOT INFORMATION
LENGTH
HARTING P/N

- 3.) CABLE IS 100% PERFORMED HI-POT TEST (300VDC) AND CONTINUITY TEST
- 4.) CABLE IS PLACED INTO A PLASTIC BAG WITH A LABEL ON IT.

33 60 211 020 0094	20 m
33 60 211 015 0093	15 m
33 60 211 010 0092	10 m
33 60 211 005 0091	5 m
33 60 211 002 0090	2 m
33 60 211 001 0089	1 m
33 60 214 500 0088	0.5 m
<i>Part-No.</i>	<i>Dim. L</i>

All Dimensions in mm Original Size DIN A 3			Techn. Character.			Free size tolerances		
Mod.	Da.t.	Na.me	Detail.	Da.t.	Na.me	/	Har-mik 36p bellow male with shielded plastic hood double ended cable assembly, L=***m	
			Insp.					
			Stand.					
ZHUHAI HARTING LIMITED							TB 33 60 21x xxxx 00xx	Page
						Sub.	/	