


- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. RATING: 5A @120VAC OR 28VDC  
2A @250VAC
  5. ELECTRICAL LIFE: 50,000 make-and-break cycles at full load.
  6. INSULATION RESISTANCE: 1,000M ohm min.
  7. DIELECTRIC STRENGTH: 1000V RMS @sea level
  8. OPERATING TEMP.: -30°C to 85°C
  9. 2002/95/EC (ROHS) COMPLIANT
  10. HARDWARE TO BE SUPPLIED BULK:
    - T100011-LOCK WASHER QTY-1
    - T100002-LOCK RING QTY-1
    - T100000-HEX NUT QTY-2
    - T100016-"O" RING QTY-1



CIRCUIT: SPDT  
CONTACT CONFIGURATION

SWITCH FUNCTION			
PDS. 1	PDS. 2	PDS. 3	
<DN>	OFF	<DN>	
2-3	OPEN	2-1	

( ) = MOMENTARY

B	16846	FIXED HARDWARE NOTES	1/10/07	TN
A	16806	RELEASED FOR PRODUCTION	12/28/06	TN
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE		DATE	DR	DWG	REV
100SP4T1B9MIQEH		2:1		1/10/2007	TN	ST114017	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

