

## Surge protection device - BXT-N4X 4-WIRE - 5603514

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Wall-mount, NEMA 4X enclosure with four conductor protection for a 2-core floating signal circuit and 120 V AC powered transmitters.

### Key commercial data

Packing unit	1 PCE
Minimum order quantity	10 PCE
GTIN	 4 046356 410472
Custom tariff number	85363030
Country of origin	GERMANY

### Technical data

#### Note:

Trade restriction	The products are offered exclusively for export outside the EU and the European Economic Area.
-------------------	--

#### General

Ambient temperature (operation)	-40 °C ... 85 °C
Mounting type	Wall mounting
Degree of protection	IP66 / NEMA 4X
Width	160 mm
Height	90 mm

#### Protective circuit, information technology

Nominal voltage $U_N$	120 V AC (Power)
Nominal voltage $U_N$	24 V AC (Signal)
Max. operating voltage $U_{max}$	150 V AC (Power)
Max. operating voltage $U_{max}$	28 V DC (Signal)
Nominal current $I_N$	20 A (Power)
Nominal current $I_N$	450 mA (Signal)

## Surge protection device - BXT-N4X 4-WIRE - 5603514

### Technical data

#### Protective circuit, information technology

Max. discharge surge current $I_{max}$ (8/20) $\mu$ s maximum (Core-Core)	10 kA
Max. discharge surge current $I_{max}$ (8/20) $\mu$ s maximum (Core-Earth)	10 kA
Resistance in series	2.2 $\Omega$

#### Power supply, general

Connection type IN	Screw connection
Connection type OUT	Screw connection
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

#### Standards (protective circuit, information technology)

Standards/regulations	IEEE C62.36
-----------------------	-------------

### Articles in set

#### Type 3 surge protection device - PT 2-PE/S-120AC/FM - 2856812



Pluggable type 3 arrester (device protection) for single-phase power supply networks with separate N and PE (3-conductor system: L1, N, PE) with remote indication contact.

#### Surge protection connector - PT 1X2-24DC-ST - 2856032



PT protective connector with protective circuit for a 2-wire floating signal circuit. HART-compatible.

# Surge protection device - BXT-N4X 4-WIRE - 5603514

## Articles in set

Surge protection base element - PT 1X2-BE - 2856113



Base element for protective plug PT with protective circuit for a 2-core floating signal circuit. Mounting on NS 35/7.5 und NS 35/15, housing width: 17.5 mm.

## Classifications

### ETIM

ETIM 4.0	EC000943
ETIM 5.0	EC000943

### UNSPSC

UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620
UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610

### eCl@ss

eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807

## Drawings

Circuit diagram

