

Part Number: 9907



Thinnet 10BASE2, #20, FPO, Duobond II+TC Braid, PVC Jkt, CM

Product Description

IEEE 802.3 Ethernet Thinnet 10BASE2, 20 AWG stranded (19x32) .037" tinned copper conductor, foam polyethylene insulation, Duobond® II (100% coverage) + an overall tinned copper braid shield (93% coverage), PVC jacket.

Technical Specifications

Product Overview

Suitable Applications:	Thin Ethernet
------------------------	---------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
20	19x32	TC - Tinned Copper	0.037 in	1

Conductor Count:	1
Conductor Size:	20 AWG

Insulation

Material	Nominal Diameter
FHDPE - Foamed High Density Polyethylene	0.102 in

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Aluminum/Polyester/Aluminum	Bonded Duofoil®	100 %
Braid	2	TC - Tinned Copper		93 %

Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.185 in
	0.279 in

Electrical Characteristics

Conductor DCR

Max. Conductor Loop	Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
15.24 Ohm/1000ft	8.8 Ohm/1000ft	5.8 Ohm/1000ft	5.8 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Shield
25.4 pF/ft

Shielding:	Foil + Braid(s)
------------	-----------------

Inductance

Nominal Inductance
0.27 µH/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance
50 Ohm	± 2 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.43 dB/100ft
10 MHz	1.3 dB/100ft
50 MHz	2.91 dB/100ft
100 MHz	4.2 dB/100ft
200 MHz	6.1 dB/100ft
400 MHz	8.9 dB/100ft
700 MHz	12.1 dB/100ft
900 MHz	13.9 dB/100ft
1000 MHz	14.8 dB/100ft

Delay

Max. Delay Skew	Nominal Delay	Nominal Velocity of Propagation (VP) [%]
80 ns/100m	1.27 ns/ft	80 %

Voltage

UL Description	UL Voltage Rating
	300 V RMS
UL AWM Style 1354	30 V RMS

Electrical Characteristics Notes:	UL AWM 1354: 30 V RMS
-----------------------------------	-----------------------

Temperature Range

UL Temp Rating:	60°C
Operating Temp Range:	-40°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	23 lbs/1000ft
Max Recommended Pulling Tension:	45 lbs
Min Bend Radius/Minor Axis:	2 in

Standards

Customer Part Number Reference Spec:	DEC Part No. 17-01248-00
NEC/(UL) Specification:	CL2, CM
CEC/C(UL) Specification:	CM
UL AWM Style:	1354 (30 V 60°C)
ISO/IEC Compliance:	8802.3 10Base2
CPR Euroclass:	Eca
IEEE Specification:	802.3 10Base2
RG Type:	58A/U Type
RG / Series Type:	58A/U Type
Other Standards:	ISO8802.3 10Base2

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 UL Loading
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	82907, 89907

Part Number

Variants

Item #	Color	Footnote
9907.001000	Gray	
9907.00152	Gray	
9907.00305	Gray	
9907.00500	Gray	
9907.00U305	Gray	
9907 E4X1000	Gray	C
9907 E4X1640	Gray	C
9907 E4X2500	Gray	C
9907 E4X3280	Gray	C
9907 E4X500	Gray	
9907 E4X5000	Gray	
9907 E4XU1000	Gray	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.