

## Support bracket - AB-SK-D TOP INSULATED - 3062087

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Support bracket, Bracket for busbars, set every 20 cm, length: 155.8 mm, width: 5.2 mm, number of positions: 2, color: gray



### Why buy this product

- For mounting SK and SKS shield connection clamps
- Can be labeled with zack marker strip and KLM terminal strip markers
- Compact design with 5.2 mm pitch
- Parking option for bridges and plugs
- The 3 x 10 mm rail can be mounted in the supports vertically, horizontally, and at a 45° angle for optimum conductor placement
- For user-friendly shield connection, especially for single and multi-level terminal blocks and devices with a front connection



### Key Commercial Data

Packing unit	10 STK
GTIN	
GTIN	4046356591850

### Technical data

#### Dimensions

Length (b)	155.8 mm
Width (a)	5.2 mm

#### General

Color	gray
Flammability rating according to UL 94	V0
Material	PA
Insulating material	PA

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

# Support bracket - AB-SK-D TOP INSULATED - 3062087


## Technical data

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Drawings

Dimensional drawing



Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>