


RECOMMEND P.C.B. LAYOUT



CIRCUIT: SPDT CONTACT CONFIGURATION

SWITCH FUNCTION			
PDS. 1	PDS. 2	PDS. 3	
DN	NONE	DN	
2-3	DPEN	2-1	

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
 3. RATING: 3 Amps @120VAC or 28VDC; 1.5 Amp @250VAC.
 4. ELECTRICAL LIFE: 30,000 make-and-break cycles at full load.
 5. INSULATION RESISTANCE: 1,000M Ohms min.
 6. DIELECTRIC STRENGTH: 1,000 V RMS @sed level.
 7. OPERATING TEMP.: -30°C to 85°C

REV. B	10214	REVISED & REDRAWN	5/11/99	CHKD
REV. A	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE		DATE	DR	DWG	REV
400 MSP-1 R1/Blk, VS2 Q E		2:1		7/30/96	MM	T411010	B



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED