



NOTES:

- METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
- INSULATORS: PBT GF UL 94 V-0, GREEN
- SIGNAL CONTACTS: COPPER ALLOY
PLATING: GOLD FLASH over NICKEL
- NO CONTACTS ON POS. A1 + A2
- THREADED LOCKS: COPPER ALLOY; min.200µin TIN over 80µin NICKEL
- METAL BRACKETS: ZINC DIE CAST; 300µin COPPER/40-120µin NICKEL/120-200µin TIN
- P.C.B. HOLE DRILLINGS ON SHEET 2
- MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
- CONNECTOR IS PART MARKED: 3017W2PAT99P20X CONE C ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

		tolerance		scale:	2:1 (5:1)
			dim. in mm	material:	SEE NOTES
		date	name	title:	
		drawn 29.05.12	Henneboel	D-SUB COMBINATION MALE 90°	
		appd. 29.05.12	Koch	17W2P	
		norm		with threaded lock and metal bracket	
		d-old		dwg no:	DIN-A3
a	Original			13K1A3979	sh: 1/2
rev.	description	date	name	part no:	3017W2PAT99P20X



