

ZFKDSA 1,5-7,62

Order No.: 1706727

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1706727>

PC terminal block, Nominal current: 16 A, Nom. voltage: 250 V, Pitch:
7.62 mm, Number of positions: 1, Type of connection: Spring-cage
connection, Conductor/PCB connection direction: 45 °, Color: green

Commercial data	
EAN	4017918136666
Pack	50 pcs.
Customs tariff	85369010
Weight/Piece	0.001715 KG
Catalog page information	Page 44 (CC-2005)

Product notes

WEEE/RoHS-compliant since:
01/01/2003



[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Certificates / Approvals



Certification

CCA, CSA, CUL, KEMA, UL

CSA

Nominal voltage U_N	300 V
Nominal current I_N	10 A
AWG/kcmil	28-12

CUL

Nominal voltage U_N	300 V
Nominal current I_N	10 A
AWG/kcmil	26-12

UL

Nominal voltage U_N	300 V
Nominal current I_N	10 A
AWG/kcmil	26-12

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;