

## Industrial PC - VL PPC 6015 JS 01 - 2913184

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

IPC with touch screen



### Key commercial data

Packing unit	1 PCE
Custom tariff number	84714100
Country of origin	Taiwan

### Technical data

#### Dimensions

External dimension, width	410 mm
External dimension, height	309 mm
External dimension, depth	96 mm
Installation dimension, width	386.6 mm
Installation dimension, height	285.6 mm

#### Display

Display	38.1 cm/15" TFT
Resolution	1024 x 768 Pixel (XGA)
Backlighting	CCFL
Display backlight MTBF	50000 h
Touch screen	Resistive industrial touch screen
Colors	16.2 million

#### Computer data

Processor	Intel® Core™2 Duo L7400 1,5 GHz
RAM	2 GB DDR SODIMM
Processor fan	Without fan
Mass storage	2.5" HDD, min. 250 Gbytes (SATA)
Graphics card	On-board graphics chip (AGP)

# Industrial PC - VL PPC 6015 JS 01 - 2913184

## Technical data

### Computer data

Interfaces	COM 1 (V.24 (RS-232)), 1x DVI-D, 1x VGA, 4x USB, 2x CompactFlash®
Network	2x Ethernet (10/100/1000 Mbps), RJ45
Operating systems	without
Realtime clock	Yes (battery-backed)
Service life of battery	5 years (typical)
Slots	without
Power supply unit	24 V DC ±20%

### Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	5 °C ... 55 °C (Configuration options can affect the operating temperature. See user manual for details)
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 % (no condensation)
Permissible humidity (storage/transport)	5 % ... 95 % (no condensation)
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

## Classifications

### eCl@ss

eCl@ss 4.0	27360103
eCl@ss 4.1	27360103
eCl@ss 5.0	27360103
eCl@ss 5.1	27242401
eCl@ss 6.0	19200102
eCl@ss 7.0	19200102

### ETIM

ETIM 3.0	EC001413
ETIM 4.0	EC001413
ETIM 5.0	EC001414

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404

# Industrial PC - VL PPC 6015 JS 01 - 2913184

## Classifications

### UNSPSC

UNSPSC 13.2	43201404
-------------	----------

## Approvals

### Approvals

---

#### Approvals

UL Listed / cUL Listed / cULus Listed

---


Ex Approvals


---


Approvals submitted

---

### Approval details

UL Listed 

cUL Listed 

cULus Listed 

## Accessories

Accessories

Mounting material

## Industrial PC - VL PPC 6015 JS 01 - 2913184

### Accessories

Removable hard drive tray - HDD TRAY KIT - 2913185



Removable hard drive tray for Valueline IPC

---

### Storage medium

Memory card - VL 512 MB CF - 2913154



CompactFlash® card, pluggable, 512 MB

---

Memory card - VL 1 GB CF - 2913155



CompactFlash® card, pluggable, 1 GB

---

Memory card - VL 2 GB CF - 2913156



CompactFlash® card, pluggable, 2 GB

---

Memory card - VL 4 GB CF - 2913157



CompactFlash® card, pluggable, 4 GB

---

## Industrial PC - VL PPC 6015 JS 01 - 2913184

### Accessories

Memory card - VL 8 GB CF - 2913158



CompactFlash® card, pluggable, 8 GB